







PRZEKROJE POPRZECZNE ZBIORNIKA




















scale 1:100

[illegible]

	total weight	total length	total width
15.84	268.70		
11.61	264.40		
11.17	264.16		
7.14	263.54	263.54	
4.32	263.48	263.11	
0.00	263.40	263.07	
10.00	263.20	263.01	
14.73	263.20	263.00	
20.00	263.20	263.00	
25.90	263.10	263.02	
30.00	263.20	263.04	
32.57	263.30	263.05	
34.85	263.38	263.38	
38.40	263.90		
51.07	264.40		
46.92	265.50		

[illegible]

пр. 261,00			
номер профилеина	глубина откоса	глубина откоса	глубина откоса
15,41	265,47		
10,83	264,40		
10,28	264,15		
6,47	263,73	263,73	
4,21	263,68	263,48	
0,00	263,60	263,32	①
10,00	263,40	263,12	②
13,92	263,34	263,10	263,40 263,10
20,00	263,40	263,11	③
25,97	263,40	263,13	
28,93	263,30	263,15	
30,00	263,36	263,16	④
33,20	263,55	263,18	
34,04	263,60	263,33	
36,94	263,85	263,85	
38,67	264,40		
41,18	265,20		

 		 		 		 		 		 		 		 		 																																																																							
---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	--	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--

Pr 261,00		
grubość profilowania	grubość izolacji	domiar
266,28	264,40	15,06
264,33	264,40	10,58
263,82	264,33	10,42
263,40	263,93	7,30
263,41	263,82	0,95
263,41	263,81	0,00
	263,80	0,21
263,58	263,58	5,99
264,16	264,16	7,00
264,18	264,18	10,00
264,18	264,18	10,38
263,70	263,70	11,03
263,24	263,60	20,00
263,20	263,55	24,51
263,26	263,50	30,00
263,41	263,59	35,11
263,62	263,62	36,70
263,94	263,94	39,09
264,40	264,40	40,33
264,80	264,80	41,40

linia	przebieg liniowej	warunki projektowa	PP 251,00
14,96	265,60		
12,28	264,60	264,60	
10,97	264,56	264,40	
3,59	264,34	263,90	
0,00	264,23	263,94	
4,12	264,10	264,10	
5,10	264,40		
7,54	265,15		
10,00	265,19		
10,76	265,20		
12,41	264,40		
13,03	264,10	264,10	
20,00	263,94	263,73	
21,66	263,90	263,67	
28,79	263,90	263,52	
30,00	263,66	263,50	
31,30	263,83	263,50	
35,89	263,70	263,55	
43,41	263,90	263,66	
50,09	264,36	264,36	
50,18	264,40		
56,89	267,23		