

# TABELA JEZDNI DROGI

m	szer.	średnia szer.	odległość	powierzchnia			krawężniki	
				w-wa wyrówn. KŁSM śr. 10cm	pełna podbudowa	kostka bet. gr. 8cm	12x25cm	15x30 lub 15x22cm
	[m]	[m]	[m]	[m <sup>2</sup> ]	[m <sup>2</sup> ]	[m <sup>2</sup> ]	[m]	[m]
0,00	19,50	zmienna	10,44		81,20	81,20	28,9	19,50
10,44	5,00							
		5,00	370,26		1 851,30	1 851,30	740,52	
380,70	5,00	5,00	13,80		69,00	69,00		27,60
394,50	5,00	5,00	18,20	54,60	36,40	91,00		36,40
412,70	5,00	5,00	2,90	8,70	5,80	14,50	2,90	2,90
415,60	5,00	5,00	95,30	285,90	190,60	476,50	190,6	
510,90	5,00	4,75	10,00	30,00	17,50	47,50	20,0	
520,90	4,50	4,50	85,10	255,30	127,65	382,95	170,2	
606,00	4,50							
Razem:			<b>606,00</b>	<b>634,50</b>	<b>2 379,45</b>	<b>3 013,95</b>	<b>1 153,12</b>	<b>86,40</b>