

Temat: Warzymice, rejon ul. Turkusowej - Wrzosowej

Obliczenie wytrzymałości na ścinanie T_{max}
dla warstwy geotechnicznej IV

Wartość normowa T_{max} 193,250

Współczynnik materiałowy 1- 0,043943691

Wartość obliczeniowa T_{max} 173,925

Nr otworu	Głębokość badania	Wartość T_{max}	$T_{max} - T_{max(n)}$	$(T_{max} - T_{max(n)})^2$
2	2,0	184	-9,25000000	85,56250000
2	2,5	187	-6,25000000	39,06250000
2	3,0	197	3,75000000	14,06250000
2	3,5	197	3,75000000	14,06250000
2	4,0	204	10,75000000	115,56250000
5	1,6	184	-9,25000000	85,56250000
5	2,0	184	-9,25000000	85,56250000
5	2,5	184	-9,25000000	85,56250000
9	1,5	184	-9,25000000	85,56250000
9	2,0	187	-6,25000000	39,06250000
9	2,5	197	3,75000000	14,06250000
9	3,0	197	3,75000000	14,06250000
9	3,5	204	10,75000000	115,56250000
9	4,0	207	13,75000000	189,06250000
15	7,5	197	3,75000000	14,06250000
18	3,5	184	-9,25000000	85,56250000
18	4,0	187	-6,25000000	39,06250000
18	4,5	197	3,75000000	14,06250000
18	6,6	197	3,75000000	14,06250000
18	7,0	204	10,75000000	115,56250000
18	7,5	204	10,75000000	115,56250000
18	8,0	211	17,75000000	315,06250000
19	3,0	184	-9,25000000	85,56250000
19	3,0	184	-9,25000000	85,56250000
20	1,1	184	-9,25000000	85,56250000
20	1,5	187	-6,25000000	39,06250000
20	2,0	197	3,75000000	14,06250000
20	2,5	197	3,75000000	14,06250000
Razem		5411		2019,25000000
Ilość badań		28		