









ZESTAWIENIE STOLARKI OKIENNEJ

| SYMBOL | 35/25 | 88/125 | 75/200 | 84/200 | 122/168 | 128/168 | 132/168 | 145/200 |
|--------------------------------|--|---|---|---|---|---|---|---|
| SCHEMAT |  |  |  |  |  |  |  |  |
| Szerokość So w świetle muru | 350 | 880 | 750 | 840 | 1220 | 1280 | 1320 | 1450 |
| Wysokość Ho w świetle muru | 250 | 1250 | 2000 | 2000 | 1680 | 1680 | 1680 | 2000 |
| Piwnica | 4 | 7 | | | | | | |
| Parter | | | 1 | 2 | | 1 | 15 | 8 |
| I piętro | | | | | | 1 | 17 | |
| II piętro | | | | | 2 | | 17 | |
| RAZEM | 4 | 7 | 1 | 2 | 2 | 2 | 49 | 8 |
| Współczynnik U | U<=0,9 W/m2K | U<=0,9 W/m2K | U<=0,9 W/m2K | U<=0,9 W/m2K | U<=0,9 W/m2K | U<=0,9 W/m2K | U<=0,9 W/m2K | U<=0,9 W/m2K |
| UWAGI | Okna PCV z profilu 5 komorowego, wyposażone w zestaw 3 szybowy. Wszystkie okna wyposażone w nawiewniki higrosterowane. Okna z dwoma zaczepami antywyważeniowymi, klamki aluminiowe. Okna w kolorze antracyt. Przed zamówieniem stolarki wymiary otworów sprawdzić na budowie. | | | | | | | |

Rys. nr A-11

| | | | |
|---------------|---|---------|---------|
| OBIEKT | BUDYNEK URZĘDU GMINY ROGOWO | | |
| ADRES | dz. nr 448/3, 361/1, obręb Rogowo, gm. Rogowo | | |
| NAZWA RYSUNKU | ZESTAWIENIE STOLARKI OKIENNEJ | Skala: | 1:50 |
| | | Data: | 05.2024 |
| PROJEKTANT | inż. Aleksander Poczatenko Upraw. bud. 489/72 Bg | Podpis: | |
| OPRACOWAŁ | inż. Piotr Kamiński | Podpis: | |